



INFRARED ILLUMINATOR - 40M

PRH-5440/5840



66-5840CSE

INSTRUCTION MANUAL

FEATURES :

- Indoor/Outdoor installation.
- High efficiency infrared LED, radiant distance
 - 40 meters.
- Sensor auto activate infrared LED under 10lux light level.
- Aluminum housing case with IP66 rating.
- Improve the image quality in low-light situation and in complete darkness.
- Aluminum PCB for fast heat dissipation.

SPECIFICATION :

INFRARED ILLUMINATOR		
	PRH-5440	PRH-5840
out Voltage	AC24V (±10%)	AC90~260V
istance	40M (131ft)	
Peak Wavelength	850nm 12 Units	
Quantity		
Angle	20 °	
Power On	Sensor Au	to Control
	ϕ 88 Heat Resistant Glass	
	IP66	
ion	Aluminum	
nsumption	7.2W	
Temperature	-20°C ~+60°C (-4°F ~+140°F)	
n	ϕ 100 x 185 mm	
	1060g	
	ut Voltage istance Peak Wavelength Quantity Angle Power On ion nsumption	PRH-5440ut VoltageAC24V (\pm 10%)istance40M (Peak Wavelength40M (Peak Wavelength12 UAngle20Power OnSensor AuPower OnSensor Auion ϕ 88 Heat ReionAlumnsumption7.2Temperature $-20^{\circ}C \sim +60^{\circ}C$ n ψ 100 x

* Any attempt to disassemble the illuminator may hamper the waterproof ability of the illuminator.

* Design and specifications are subject to change without notice.

