


# QH-D8416AM

1080P AHD DVR


**QIHAN**  
Creation for Safe Life



## Feature

- Support AHD, Analog and IP Video input
- AHD and Analog input are self-adaptive
- Third-party IP cameras supported with ONVIF V2.4 conformance
- Support 1 or 2 SATA HDDs, each HDD is up to 4TB, 2 USB2.0
- 4/8 channel synchronous playback
- Simultaneous HDMI and VGA output, the resolution is up to 1080P
- Support free DDNS, e.g. HDCCTVDDNS
- Support UPnP、NTP、DHCP、PPPoE、RTSP
- Support mobile app access
- Up to 500 meters long distance stable and high quality 1080P video transmission
- Support record with 1080N ( 960\*1080 ) resolution, which will save half of the HDD disk space compares to 1080P.

## Dimensions



Unit: mm

## Technical Specifications

Model NO.	QH-D8416AM
OPERATION SYSTEM	LINUX
<b>VIDEO</b>	
VIDEO SYSTEM	NTSC/PAL Switch Selectable
INPUT	BNC*8,1.0Vp-p,75ohm
HDMI OUTPUT	1 HDMI Output
VGA OUTPUT	1 VGA Output
<b>AUDIO</b>	
INPUT	8CH, RCA
OUTPUT	1CH, RCA
TALK BACK	YES
<b>CONTROL</b>	
MOUSE	2*USB2.0
<b>STORAGE</b>	
BUILD IN INTERFACE	4 SATA Interfaces, Up to 24TB
<b>DISPLAY</b>	
DIVISION	1, 4, 9, 16
ZOOM	Preview&Playback Zoom Support
<b>RECORDING</b>	
COMPRESSION	H.264(High profile)
RECORDING MODE	Manual/Schedule/Motion Detection/Sensor
ENCODING ABILITY	16* 1080P@12fps
DECODING ABILITY	8* 1080P@12fps
RESOLUTION	Analog: 16* 1080P; 16* 720P; Hybird: 2* 1080P(Analog) +2*1080P(Network); 4* 720P(Analog) + 4*720P(Network); Network: 4*1080P, 1*1080P+8*720P, 20*960H;
QUALITY	Lowest, Lower, Low, High, Higher, Highest
<b>PLAYBACK</b>	
SYNC PLAYBACK	1 to 8 (Max 8 CH)
SPEED	Normal, FF(1X, 2X, 3X, 4X), RF(1X, 2X, 3X, 4X), Slow (1X, 2X, 3X, 4X)
SEARCH MODE	Event, Channels and Calendar
<b>COMMUNICATION</b>	
REMOTE ACCESS	IE ( 6.0 and above), Chrome, Firefox, ISS ( Windows XP/WIN7/WIN8 ), ISS MOBILE2 ( IOS, Android )
REMOTE OPERATION	Remote View, Remote Playback, Remote Setup
NETWORK SERVICE	TCP/IP, PPPOE, DDNS, FTP, NTP, UPNP, SMTP, RTSP, HTTP
MOBILE DEVICE	iPhone, iPad, Android
3G EXTERNAL MODULE	Yes, with USB 2.0 Port
WAN RJ45	10/100Mbit/s
WIFI EXTERNAL MODULE	Yes, with USB 2.0 Port
GUI INTERFACE	Supported GUI 16 Bit True Color
PTZ PROTOCOL	PELCO-D, PELCO-P, etc 21 Kinds of Protocol
<b>BACKUP</b>	
EXTERNAL	2*USB2.0
NETWORK	YES
FILE FORMAT	H264/AVI
<b>GENERAL</b>	
ALARM IN/OUT	16/4
RS-485	1
RS-232	1
OPERATION TEMPERATURE	10°~40°
WORKING HUMIDITY	10% ~ 90%
POWER SUPPLY	12V, 6A
POWER CONSUMPTION	<15W (Without HDD)
UNIT DIMENSION(mm)	W380*D368*H74mm
WEIGHT	1800g