

AS21.5LED

21.5" (16:9) LED Monitor

AS21.5LED

Panel Type	21.5" (16:9) LED Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	476.64 (H) x 268.11 (V) mm
Pixel Pitch	0.24825 (H) x 0.24825 (V) mm
Bezel Thickness	Sides: 22mm Top: 23mm Bottom: 45mm
Contrast Ratio	10000 : 1
Brightness	250 cd/m ²
Response Time	5ms
Viewing Angle	U/D: 80° / 80°, L/ R: 85° / 85°
Display Colours	16.7 M
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9 Ratio with 4:3 Function
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1 Left x 1, 3W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	10 % - 90 %
Work Temperature	0°~40°C(32° ~104°F)
Volume +/- Power On/Off	Yes

IN/OUT INTERFACE

Video Interface	HDMI x1 VGA x 1 BNC x 2 In / BNC x2 Out
Audio Interface	Audio in x 1, Audio L x 1, Audio R x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	100 x 100mm
Stand Type	Desktop
Colour	Black
Button Position	Top, Back
Packing Dimension	626(W) x 475(H) x 177(D)
NET Weight	5.25 Kg
GROSS Weight	6.79 Kg



POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 35W in "ON" Mode

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, PIP, POP

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish, Turkish, Dutch and Czech

ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Remote Control / Screws For Stand And User Manual

Unit: mm

