

# RYK-2397, 2379, 2349 / 2J97, 2J79, 2J49

## Mini Dome Camera

### FEATURES

- 420~700 TV Line
- Support AWB, AGC, AES and DNS
- 3-AXIS Mechanism for Free Lens Rotation




RYK-23xx




RYK-2Jxx  
(Vandal Proof)

### DIMENSIONS



RYK-23xx



RYK-2Jxx

### SPECIFICATIONS

Model No.	RYK-2397	RYK-2349	RYK-2379
	RYK-2J97	RYK-2J49	RYK-2J79
<b>Image Device</b>	1/3" Color Sony Exview HAD II CCD	1/3" Color Sony Super HAD II CCD	1/3" Color Hi-Res. CCD
<b>Picture Elements</b>	NTSC: 976x494, PAL: 976x582	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582
<b>Resolution</b>	700 TVL	420 TVL	540 TVL
<b>Min. Illumination</b>	0.01 Lux @ F1.2	0.05 Lux @F1.2	0.1 Lux @F1.2
<b>S/N Ratio</b>	More than 50dB		
<b>Electronic Shutter</b>	NTSC:1/60~1/100,000, PAL:1/50~1/100,000		
<b>Gamma</b>	0.45		
<b>Iris Control</b>	Fixed		
<b>Lens Furnished</b>	Board Lens 3.6mm / F2.0 (Optional:2.5/4.3/6/12)		
<b>Sync. System</b>	Internal		
<b>Video Output</b>	1 Vp-p / 75 Ohms		
<b>Power Supply</b>	DC12V±10%		
<b>Power Consumption</b>	95mA	120mA	75mA
<b>Operating Temp.</b>	-10°C ~ 50°C		

# RYK-2497, 2449, 2479


## Medium Dome Camera

### FEATURES

- 420~700 TV Line
- Support AWB, AGC, AES and DNR [RYK-2497]
- 3-AXIS Mechanism for Free Lens Rotation
- Optional:VF: Vari-Focal DC Lens 3.7~12mm (without ICR)  
VR: Vari-Focal DC Lens 3.7~12mm(with ICR)  
VT: Vari-Focal Fixed Lens 3~9mm



### DIMENSIONS



### SPECIFICATIONS

Model No.	RYK-2497	RYK-2449	RYK-2479
	<b>Image Device</b>	1/3" Color Sony Exview HAD II CCD	1/3" Color Sony Super HAD II CCD
<b>Picture Elements</b>	NTSC: 976x494, PAL: 976x582	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582
<b>Resolution</b>	700 TVL	420 TVL	540 TVL
<b>Min. Illumination</b>	0.01 Lux @ F1.2	0.05 Lux @ F1.2	0.1 Lux @ F1.2
<b>S/N Ratio</b>	More than 50dB		
<b>Electronic Shutter</b>	NTSC:1/60~1/100,000, PAL:1/50~1/100,000		
<b>Gamma</b>	0.45		
<b>Iris Control</b>	DC Drive (For VF Type Only)		
<b>Lens Furnished</b>	Board Lens (BL) : 3.6mm / F2.0 (Optional : 4.3 / 6 / 12mm)		
<b>Sync. System</b>	Internal		
<b>Power Supply</b>	DC12V±10%		
<b>Power Consumption</b>	95mA (35mA with VF Lens)	120mA (35mA with VF Lens)	75mA (35mA with VF Lens)
<b>Operating Temp.</b>	-10°C ~ 50°C		