Vigor540

Wireless 11g CardBus Adapter

- Standards Compliance IEEE802.11g, IEEE802.11b
- Transmission Rate 54 Mbps





Vigor540 WLAN CardBus Adapter

	•		
CardBus	32-bit CardBus Type II		
■ LED	Status		
■ Antenna	ntenna Internal printed antenna		
RADIO CHARACTERISTICS			
Standard	IEEE 802.11b and IEEE 802.11g		
Frequency Bands	2.412~ 2.497GHz ISM Band		
	802.11b: 11Mbps and 5.5Mbps CCK; 2Mbps: DQPSK;		
■ Modulation Tech	1Mbps: DBPSK		
	802.11g: OFDM		
Media Access Protocol	CSMA/CA with ACK		
Transmit Power	16.5 dBm @ Nominal Temp Range		
Data Rates	802.11b: 11Mbps, 5.5Mbps, 2Mbps, 1Mbps, auto fallback		
	802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps		
ENVIRONMENTAL			
■ Temperature	0°C to 60°C(Operating),-20°C to 80°C(Storing)		
■ Humidity	95% Non-condensing		
Power Consumption	ver Consumption Tx peak 470mA @ 3.3VDC, Rx peak 330mA @ 3.3VDC		
DRIVERS & UTILITY			
Operating Systems	Windows 98SE/2000/ME/XP		
Security	64/128 Bit WEP Key; WPA supports TKIP		
CERTIFICATION	CATION WARRANTY		
FCC class B; CE Mark	■ One year limited		

PACKAGE CONTENTS

One Wireless LAN CardBus Adapter		One Setup CD-ROM with User Guide.

One Quick Installation Guide



[■] The Vigor540 is designed for the WLAN 2.4Ghz network throughout the EC region and Switzerland, with restriction in France!